



ARENA SERIES LED FLOODLIGHT

- ⚡ 500W
- ☀️ 62.500lm
- K** 4000-6500K



Product Information

Specially manufactured for provide high level and stable illumination of large areas such as sports arenas and stadiums, ports, airports, large parking lots, large warehouses, factories and their surroundings and other large areas that require floodlighting.



Product Features

- Long life up to 50,000 hours, maintenance free
- Proven most efficient in its class
- Philips LED Driver and Chip
- Colour temperatures from 4000K and 6500K
- Smooth light distribution
- Special modular design
- Light angles that can be adjusted according to needs
- Two-year money-back, five-year product warranty

Product Benefits

- Environmentally friendly lighting
- 70% reduced energy consumption
- Very durable, bright and robust
- Optimized and easy logistics and installation
- Cost-efficient
- Controlled heat emission
- Produce light similar to daylight

Application Areas



Sport Stadium



Port



Airport



Factory



Warehouse

General Informations


Color Temperature	4000K - 6500K
Driver	Yes
LED Chip & Driver	Philips
IEC Protection Class	Safety Class I
ENEC/UL Mark	On Driver
CE Mark	CE Mark
Constant Light Output	Yes

Electrical Details

Input Voltage	AC 85V - 265V
Input Frequency	50Hz
Power Factor	0.9(Nominal Power)


Dimming


Dimmable	No
----------	----



We have been innovating and manufacturing for you

We have operated for 38 years with the highest quality components and industry-leading operational experience and capability.





Lighting Performance

Luminous Flux	62500lm
Efficiency of LED Luminaires	125lm/W
Power Output	500W
LED Lifespan (hours)	50000
CRI (Color Rendering Index) RA>	>85
Light Angle (°)	from 15° to 120° according to requirements

Mechanics and Material

Housing Material	Aluminum
Optical Material / Lens	Polycarbonate
Length	550mm
Width	190mm
Height	250mm
Fixing Material	Aluminum/Steel

Product Info


Product Order Code	ARENA500
Product	ARENA Series 500W LED Floodlight
Quantity in Box	1
SKU Number	ARENA500-23-625
Net Weight (piece)	23kg

Safety and Impact Resistance

IP Protection Degree	IP66
Impact Resistance Class	IK08

Terms of Use

Temperature Range	-35°C / 60°C
-------------------	--------------



FACTORY

MALIKÖY BAŞKENT OSB BAŞKENT BULVARI NO: 9 SINCAN
ANKARA / TURKEY

HEADQUARTERS

ÇAMLICA MAHALLESİ 145. SOKAK NO: 10 / 47
MACUNKÖY, YENİMAHALLE ANKARA / TURKEY

ISTANBUL

MEŞRUTİYET MAHALLESİ EBE KIZI SOKAK REN APT. NO: 11/9 OSMANBEY
ŞİŞLİ / İSTANBUL

ISTANBUL SHOWROOM

BEŞYOL MAHALLESİ E-5 YANYOL NO: 15-C
KÜÇÜKÇEKMECE / İSTANBUL

EUROPE

SCHÄFTLARNSTRASSE 10, SENDLING 81371
MUNICH / GERMANY

AFRICA

ADEBAYO DOHERTY ROAD, ADMIRALTY WAY, LEKKI PHASE 1
LAGOS / NIGERIA

MIDDLE EAST

HAMMED AL JASER ST. KADOUR BUSSINESS CENTER 3RD FLOOR OFFICE: 18
JEDDAH / KSA

SOME OF OUR REFERENCES



MADE IN
TÜRKİYE



As Soli Lighting, we are constantly developing and improving our products according to the latest technology and innovations. Therefore, all product descriptions in this catalog are a general guideline and we may change specifications from time to time without notice or public notice for product improvement purposes. All data contained in this data sheet presents only general characteristics of the product referred to and does not form part of any contract. ©Depar Group 1984-2022. All rights reserved.